

ECO8 - Lincat Electric Counter-top Convection Oven - W 787 mm - D 644 mm - 3.0 kW Cook your way with this versatile 3kW Lincat Electric Convection Oven.

- Designed to meet the needs of even the most demanding professional kitchen. Versatile and great for roasts, pizzas, pies and bakery products
- The excellent twin fan air circulation system delivers a highly efficient air circulation ensuring consistent, even and faster cooking times
- Accommodates 1/1GN containers for convenient operation
- Fast heat up from cold saves time and money and fast recovery times
- Water injection facility gives a professional finish to breads and pastries. The useful cook and hold facility reduces oven temperature to 80 degs C at end of cooking period
- Double-glazed door for energy efficiency
- Stackable for added flexibility and to make the best of use of floorspace
- Robust stainless steel construction

Specifications

Specifications				
Summary		Power and Performance		
Brand	Lincat	Total Power kW	3.0	
Range	Specialist	Temperature Range °C	50-300	
Power Type	Electric	IP Rating	IP23	
Unit Type	Counter-top	Controls Position	Right hand side	
Available in UK Only	No	Temperature Control	Mechanical	
UK Warranty	2 Years Parts and Labour Warranty	Timer Range mins	1-45; 1-180	
Export Warranty	Contact your local dealer	Oven Rating kW	3.0	
GTIN	5056105101673			



		·	·
Stackable	Yes	Gastronorm Capacity	3 x GN1/1
Feet Height/Type	25mm/adjustable	Euronorm Capacity	3
Continuous Plug-In Door Seal	Yes	Shelf Spacing mm	110
Removable Inner Door Glass	Yes	Sheet Pan Capacity	3 x 460 mm x 330 mm
Handle Type	Pendulum	Capacity Litres	130.0
Vented Door	Yes		
Reversible Door	No		
Door Type	Left Hinged		
Phased Cooking	No		
Shelf Timer(s) (Number)	No		
Grill Element/Mode	No		
Core Temp Probe	No		
Steam Injection	Yes		
Fan(s) Speed	1		
Fan(s) Type	Single Direction		
Number of Fan(s)	2		
Euronorm Compatible	Yes		
Sheet Pan Compatible	Yes		
Removeable Shelf Guides	Yes		
Manual Mode	Yes		
Programmable	No		
Timer Type	2 x Mechanical		
Number of Shelves included	3		
Number of Shelf Positions	3		
Type of Lighting	Filament Bulb		
Construction/Finish	430 S/S exterior/cavity		
GN Compatible	Yes		
Weights and Dimensions		Supply Connections	
Unit Height (External) mm	575	Requires Installation	No
Unit Width (External) mm	787	Requires Electrical Supply	Yes
Unit Depth (External) mm	644	UK 3 Pin Plug	Yes
Height (Internal) mm	430	Requires Hardwiring	No
Width (Internal) mm	600	Electrical Supply Rating Watts	3,000
Depth (Internal) mm	504	Single Phase Amps	13.0
Shelf Dimensions Width mm	530	Single Phase Voltage	230
Shelf Dimensions Depth mm	325	Water Connection Pressure Bar	0.2-10.0
Net Weight Kg	66.9	Drain Connection	No
		Water Connection	3/4" BSPT
		USB Port	No
Shipping			
Packed Weight Kg	73.59		
B 1 111 1 1	70.00		

Available Accessories

Packed Height cm Packed Width cm Packed Depth cm


ECO8/FSFloor Stand for EC08ECO8/LFSEC08 LOW FLOOR STANDEC08/SKEC08 STACKING KIT


80


Technical Picture



lincat









Lincat Limited

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

Company No: 2175448

A member company of

Customer Care

Tel: +44 1522 875500

Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536

Email: export@lincat.co.uk

Opening Hours

Monday - Friday:

8.30am - 5pm