# **SLOT TOASTERS**

The stylish Hatco Slot Toaster is built to suit all heavy-duty, every day busy kitchens, and the durable polished stainless steel is stylish for any decor. Perfect for self-serve buffet areas and lighter volume restaurants, diners, and cafes. It's a great addition to your conveyor toaster for those non-peak periods when an occasional order of toast is needed.

- Choose from either a 4 slot or a 6 slot model
- The elements are easily changed by operator, reducing service calls
- The TPU-230-4 unit enables either two slot or four slot toasting
- The TPU-230-6 unit enables either two, four, or six slot toasting
- · Timed toasting control
- · Removable crumb tray for easy cleaning
- 1829 mm cord and plug



TPU-230-4

R	VS	tock Item	See Page 75
List Price	Dimensions (W x D x H)	kW	Ship Weight
£195.	320 x 262 x 246 mm	2.0	8 kg
225.	424 x 262 x 245 mm	2.9	10 kg
Feature:			
			230V, single phase
PU-230-4:			25 W x 121 D mm
PU-230-6:			25 W x 121 D mm
			All
TPU-230-4:		1829 mm on	bottom, back right
TPU-230-6:		1829 mm o	n bottom, back lef
	£195. 225. Feature:	List Price Dimensions (W x D x H)  £195. 320 x 262 x 246 mm  225. 424 x 262 x 245 mm  Feature:  PU-230-4:	List Price         Dimensions (W x D x H)         kW           £195.         320 x 262 x 246 mm         2.0           225.         424 x 262 x 245 mm         2.9

<sup>\*</sup> Toasting capacity may vary by product. Toasting of coated products not recommended.

ONE YEAR REPAIR OR REPLACE WARRANTY, CONTACT HATCO SERVICE FOR DETAILS.

# TOASTER AMP RATINGS

	230V/1 Ø
Model	Amps
TPU-230-4	8.6
TPU-230-6	12.3







V Stock Itom see from 75

	I UAS I - IVIA	X CONVETUR TO	ASTER	N STOCK ITE	See Page 75
	Model*	List Price	Dimensions (W x D x H)*	kW	Ship Weight
/	TM-5	£564.	289 x 420 x 387 mm	1.6	16 kg
/	TM-10	754.	368 x 402 x 387 mm	2.3	19 kg
	A				

Add 203 mm to depth if using tray extension in rear. Height includes legs.

#### All Toast-Max Models Feature:

Voltage:	230V, single phase.
Capacity Per Minute* – TM-5:	3 slices.
	6 slices.
Bread Types:	Bread or Buns.
Maximum Product Size: – TM-5:	
– TM-10:	264 W x 64 H mm.
Cord Location:	1829 mm on left side of back of unit near bottom.
* Toasting capacity may vary by product. Toasting of co	ated products not recommended.

ALL TOAST-MAX METAL SHEATHED HEATING ELEMENTS WARRANTED AGAINST BURNOUT AND BREAKAGE FOR TWO YEARS.

#### TOAST-OWIK CONVEYOR TOASTER

			· · - · ·	ALDON ISS	See Page 75
	Model*	List Price	Dimensions (W x D x H)▲	kW	Ship Weight
1	TQ-405	£1372.	368 x 451 x 378 mm	2.2	22 kg
	TQ-400H	1309.	368 x 451 x 378 mm	2.1	22 kg
	TQ-400BA*	1309.	368 x 451 x 403 mm	2.2	22 kg
1	TQ-805	1663.	368 x 578 x 422 mm	3.6	28 kg
	TQ-800BA*	1490.	368 x 578 x 422 mm	3.4	28 kg
	TQ-800HBA▼	1490.	368 x 578 x 422 mm	3.4	28 kg

- ▲ TQ-405, -400H, and -400BA, add 64 mm to depth if using tray extension in rear. TQ-805, TQ-800BA and TQ-800HBA add 165 mm to depth if using tray extension in rear. Height includes legs.
- ▼ BA models toast one side only and are for bagels and buns, cut side up.

#### All Toast-Qwik Models Feature:

Voltage:	240V, single phase.		
Bread Types - TQ-405, -805:			
– TQ-400H, -400BA, -800BA, -800HBA:			
Maximum Product Size - TQ-405, -400BA, -805, -800BA:	244 W x 44 H mm.		
– TQ-800HBA:	244 W x 70 H mm.		
Cord Location:	9 mm on lower right corner on back of unit.		
* Toasting capacity may vary by product. Toasting of coated products not recommended.			
ALL TOAST-QWIK METAL SHEATHED HEATING ELEMENTS WARR	ANTED AGAINST BURNOUT AND BREAKAGE		

FOR TWO YEARS.

#### **OPTIONS AND ACCESSORIES – SEE PAGE 4**

# **CONVEYOR TOASTER AMP RATINGS**

Model	240V 50 Hz/1 Ø Amps
TM-5	6.6
TM-10	
TQ-405	9.2
TQ-400H	9.3
TQ-400BA	8.8
TQ-805	15.1
TQ-800BA	14.0
TQ-800HBA	14.0

### **CONVEYOR TOASTER OPENING DIMENSIONS**

Model Dime	nsions (W x H)
TQ-405, -400BA, -805, -800BA	254 X 51 mm
TQ-400H, TQ-800HBA	254 x 76 mm

# TOAST-MAX® AND TOAST-QWIK® **CONVEYOR TOASTERS**

Flexibility and performance are yours with any of the Hatco conveyor toasters, from the economical Toast-Max® to the high capacity Toast-Qwik®. Using conveyor speed, not temperature, to determine toasting color, allows for instant adjustment of toasting time. Toast-Max features an easy-to-use 4-position toast selector switch with Off / Toast / Buns / Stand-by. Toast-Owik features ColorGuard sensing system for consistently toasted product.



TQ-805

- Automatic Power Save Mode will reduce power consumption after 30 minutes of inactivity for TQ-405 model
- Instant and precise adjustment of toast color with electronic infinite controls that regulate top and
- Patented ColorGuard sensing system assures toast uniformity for TQ-400 and -800 series
- Power Save Mode conserves energy
- · Capacity of 180-800 slices per hour
- Opening height for H and HBA models is 76 mm, for all other models the opening height is 51 mm
- Insulation and an interior fan provide cool surface temperatures
- Efficient design of front or rear discharge allows unit to be placed where it is most convenient – for sending product to the operator side or to the customer/server side



# OPTIONS (NOT FOR RETROFIT) -







TK-105

### TOAST-RITE CONVEYOR TOASTER

Model	LIST Price	Dimensions (W X D X H)	KW	Snip weignt
TRH-65	£2104.	448 x 699 x 418 mm	4.4	29 kg
<ul> <li>Includes tra</li> </ul>	ay extension of 127 n	nm.		
All Toast-Rite	Models Feature:			
Basket Size:				254 W x 117 H mm.
Capacity Per N	/linute*:			10 slices.
Bread Types: .				Bread or Buns.
Cord Location:		1219 mm on	lower right co	rner on back of unit.
* Toasting cap	acity may vary by pro	duct. Toasting of coated products not	recommended	l.
ALL TOAST-RIT	TE METAL SHEATHED	HEATING ELEMENTS WARRANTED AG	AINST BURNO	ut and breakage
FOR TWO YEAR	RS.			

TOAST KING CONVEYOR TOASTER
-----------------------------

	TOAST KIN	G CONVEYOR TOASTER		V Stock Item	See Page 75
	Model	List Price	Dimensions (W x D* x H)	kW	Ship Weight
	TK-75	£2378.	445 x 448 x 838 mm	5.2	35 kg
~	TK-105	2535.	559 x 448 x 838 mm	7.5	40 kg
*	TK-135B	2395.	559 x 448 x 838 mm	5.0	40 kg

Includes tray extension of 89 mm.

All Toast King Models Feature:	
Voltage:	240V, single phase.
Basket Size – TK-75 (Two-slice model):	
- TK-105, -135B (Three-slice model):	368 W x 117 H mm.
Capacity Per Minute* – TK-75:	12 slices.
– TK-105:	16 slices.
– TK-135B:	22 slices.
Bread Types – TK-75, -105:	Bread or Buns.
– TK-135B:	Buns.
Maximum Product Thickness:	32 mm.
Cord Location – TK-75, -135B:	1219 mm on lower left side on back of unit.
– TK-105:	
* Tracting capacity may vary by product. Tracting of coated r	roducte not recommended

Toasting capacity may vary by product. Toasting of coated products not recommended. ALL TOAST KING METAL SHEATHED HEATING ELEMENTS WARRANTED AGAINST BURNOUT AND BREAKAGE

## **CONVEYOR TOASTER AMP RATINGS**


	240V
	50 Hz/1 Ø
Model	Amps
TRH-65	18.1
TK-75	21.8
TK-105	31.0
TK-135B	18.1

# **OPTIONS (NOT FOR RETROFIT) -**

TRH-SECURITY	£120.
TK-SECURITYControl Cover, Bracket, Mounting Hardware and Fuse Cover (TK models only)	
ACCESSORIES –	
4"LEGS	£ 40.
TK-3BSKT-TLBaskets for Jumbo 140 mm Buns (9) – 3-Slice Models only (TK-105 only)	

# TOAST-RITE® AND TOAST KING® CONVEYOR TOASTERS

Designed for mid- to high-volume and constant flow applications, Hatco's proven reliability and performance makes the TRH and TK toasters the workhorse of your operation. These toasters use conveyor speed, not temperature, to determine toast color.



- Toasts a variety of bread products
- Stainless steel construction for years of trouble-free service
- Power saving thermostat for energy savings during non-peak times
- Manual advance and speed control
- Fully insulated for cooler operation
- Multiple metal sheathed toasting elements
- Toast storage area keeps bread warm and dry
- Capacity of 480-600 slices per hour (TRH series)
- Capacity of 720-1300 slices per hour (TK series)
- Three basket access for fast loading (TK series)
- Top venting keeps heat away from the operator (TK series)

